NSN 5962-01-395-9847

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-395-9847

Maximum Power Dissipation Rating:
2.0 watts
Operating Tempurature Range:
-20.0/+85.0 degrees celsius
Storage Tempurature Range:
-55.0/+150.0 degrees celsius
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Design Function And Quantity:
1 driver
Current Rating Per Characteristic:
300.00 milliamperes peak forward surge current horsepower metric
Terminal Surface Treatment:
Terminal Surface Treatment: Solder
Solder
Solder Voltage Rating And Type Per Characteristic:
Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source
Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity:
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 printed circuit
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life:
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a Unit Of Measure:
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: