## NSN 5962-01-396-1350

Linear Microcircuit - Page 1 of 1



standards, etc.).

View Online at https://aerobasegroup.com/nsn/5962-01-396-1350

Body Length:         0.350 inches         Body Width:         0.350 inches         Body Height:         0.100 inches         Maximum Power Dissipation Rating:         1.0 watts         Operating Tempurature Range:         -55.0/125.0 degrees celsius         Storage Tempurature Range:         -65.0/125.0 degrees celsius         Breatures Provided:         Hermetically sealed and burn in and electrostatic sensitive and low noise         Inclosure Material:         Ceramic         Hout Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         22.0 volts power source         Terminal Type And Quantity:         2.0 lott Of Measure:         Voltage Rating And Type Per Characteristic:         22.0 volts power source         Terminal Type And Quantity:         2 lot of Measure:         Via         Hitc:         Na         Unit Of Measure:         Terminal Type And Quantity:         Va somi         Di	
Body Widh: 0.350 inches Body Height: 0.100 inches Maximum Power Dissipation Rating: 1.0 watts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius Features Provided: 6-6.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and electrostatic sensitive and low noise Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 4 input Design Function And Quantity: 2 amplifier, operational, general purpose Terminal Surface Treatment: Solder 2.0 volts power source Terminal Surface Treatment: 22.0 volts power source Terminal Type And Quantity: 20 leadless Sheff Life: N/a Uhit Of Measure: 	Body Length:
Oxed inches         Body Height:         0.100 inches         Maximum Power Dissipation Rating:         1.0 watts         Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Storage Tempurature Range:         -65.0/+125.0 degrees celsius         Features Provided:         Hermetically sealed and burn in and electrostatic sensitive and low noise         Inclosure Material:         Corranic         Inclosure Configuration:         Leadless flat pack         Input Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         Votage Rating And Type Per Characteristic:         20 loadless         Sheff Life:         20 leadless         Sheff Life:         Val         Detailes         Sheff Life:         Val         Dutt Of Measure:         -         -         Demilitarization:         Yas - demil/mli	0.350 inches
Body Height: 0.100 inches Maximum Power Dissipation Rating: 1.0 watts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hernetically sealed and burn in and electrostatic sensitive and low noise Inclosure Material: Ceramic Inclosure Anterial: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 4 input Design Function And Quantity: 2 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer Terminal Type And Quantity: 20 leadless Sheft Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli	Body Width:
0.100 inches Maximum Power Dissipation Rating: 1.0 watts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and electrostatic sensitive and low noise Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 4 input Design Function And Quantity: 2 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Terminal Type And Quantity: 20 leadless Sheff Life: N/a Unit Of Measure:	0.350 inches
Maximum Power Dissipation Rating:         1.0 watts         Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Storage Tempurature Range:         -65.0/+150.0 degrees celsius         Features Provided:         Hermetically sealed and burn in and electrostatic sensitive and low noise         Inclosure Material:         Ceramic         Inclosure Configuration:         Leadless flat pack         Input Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         94096-mil-std-883 standard (includes industry or association standards, individual manufactureer:         7         95096-mil-std-883 standard (includes industry or association standards, individual manufactureer:         7         95096-mil-std-883 standard (includes industry or association standards, individual manufactureer:         7         N/a         1         N/a         1         1         1         1         1         2         1         2         1         2<	Body Height:
1.0 watts         Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Storage Tempurature Range:         -65.0/+150.0 degrees celsius         Features Provide:         Hermetically sealed and burn in and electrostatic sensitive and low noise         Inclosure Material:         Ceramic         Inclosure Configuration:         Leadless flat pack         Input Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         96906-mil-std-883 standard (includes industry or association standards, individual manufactureer:         Terminal Type And Quantity:         20 leadless         Shelf Life:         Na         Unit Of Measure:         -         Demilitarization:         Yes - demil/mli	0.100 inches
Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Storage Tempurature Range:         -65.0/+150.0 degrees celsius         Features Provided:         Hermetically sealed and burn in and electrostatic sensitive and low noise         Inclosure Material:         Ceramic         Inclosure Configuration:         Leadless flat pack         Input Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         22.0 volts power source         Test Data Document:         96906-mil-std-883 standard (includes industry or association standards, individual manufactureer:         Terminal Type And Quantity:         20 leadless         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         Yes - demil/mli         Fig:	Maximum Power Dissipation Rating:
-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and burn in and electrostatic sensitive and low noise Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 4 input Design Function And Quantity: 2 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer: Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mli Fig:	1.0 watts
Storage Tempurature Range: -65.0/4150.0 degrees celsius Features Provided: Hermetically sealed and burn in and electrostatic sensitive and low noise Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 4 input Design Function And Quantity: 2 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer: Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: - - Demilitarization: Yes - demil/mli	Operating Tempurature Range:
-65.0/+150.0 degrees celsius         Features Provided:         Hermetically sealed and burn in and electrostatic sensitive and low noise         Inclosure Material:         Ceramic         Inclosure Configuration:         Leadless flat pack         Input Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         22.0 volts power source         Test Data Document:         96906-mil-std-883 standard (includes industry or association standards, individual manufactureer         Terminal Type And Quantity:         20 leadless         Shelf Life:         N/a         Unit of Measure:         -         Demilitarization:         Yes - demil/mli         Fig:	-55.0/+125.0 degrees celsius
Features Provided:         Hermetically sealed and burn in and electrostatic sensitive and low noise         Inclosure Material:         Ceramic         Inclosure Configuration:         Leadless flat pack         Input Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         22.0 volts power source         Test Data Document:         96906-mil-std-883 standard (includes industry or association standards, individual manufactureer interminal Type And Quantity:         20 leadless         Shelf Life:         N/a         Unit of Measure:         -         Demilitarization:         Yes - demil/mli	Storage Tempurature Range:
Hermetically sealed and burn in and electrostatic sensitive and low noise         Inclosure Material:         Ceramic         Inclosure Configuration:         Leadless flat pack         Input Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         22.0 volts power source         Test Data Document:         96906-mil-std-883 standard (includes industry or association standards, individual manufactureer:         Terminal Type And Quantity:         20 leadless         Shelf Life:         N/a         Unit Of Measure:            Fomiliarization:         Yes - demil/mli	-65.0/+150.0 degrees celsius
Inclosure Material:         Ceramic         Inclosure Configuration:         Leadless flat pack         Input Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         Vottage Rating And Type Per Characteristic:         22.0 volts power source         Test Data Document:         96906-mil-std-883 standard (includes industry or association standards, individual manufactureer:         Terminal Type And Quantity:         20 leadless         Shelf Life:         N/a         Unit Of Measure:         -         Penilitarization:         Yes - demil/mli         Fig:	Features Provided:
Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: I input Design Function And Quantity: I amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer: Cerminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Hermetically sealed and burn in and electrostatic sensitive and low noise
Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 4 input Design Function And Quantity: 2 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fig:	Inclosure Material:
Leadless flat pack Input Circuit Pattern: 4 input Design Function And Quantity: 2 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer in Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fig:	Ceramic
Input Circuit Pattern:         4 input         Design Function And Quantity:         2 amplifier, operational, general purpose         Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         22.0 volts power source         Test Data Document:         96906-mil-std-883 standard (includes industry or association standards, individual manufactureer)         Terminal Type And Quantity:         20 leadless         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         Yes - demil/mli	Inclosure Configuration:
4 input Design Function And Quantity: 2 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 9000-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 9000-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 9000-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 9000-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 9000-mil-std-883 statements 9000-mil-std-883 standard (includes industry or association standards, individual manufactureer statements) 9000-mil-std-883 statements 9000-mil-std-883 statements 9000-mil-std-883 statements 9000-mil-std-883 statements 9000-mil-std-883 statements 9000-mil-std-883	Leadless flat pack
Design Function And Quantity:   2 amplifier, operational, general purpose   Terminal Surface Treatment:   Solder   Voltage Rating And Type Per Characteristic:   22.0 volts power source   Test Data Document:   96906-mil-std-883 standard (includes industry or association standards, individual manufactureer treminal Type And Quantity:   20 leadless   Shelf Life:   N/a   Unit Of Measure:   -   -   Demilitarization:   Yes - demil/mli	Input Circuit Pattern:
2 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, indin standards, individual manufacture	4 input
Terminal Surface Treatment:         Solder         Voltage Rating And Type Per Characteristic:         22.0 volts power source         Test Data Document:         96906-mil-std-883 standard (includes industry or association standards, individual manufactureer in the treatment in the treatment is the treatment in the treatment is the tre	Design Function And Quantity:
Solder   Voltage Rating And Type Per Characteristic:   22.0 volts power source   Test Data Document:   96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards)   Terminal Type And Quantity:   20 leadless   Shelf Life:   N/a   Unit Of Measure:     Pemilitarization:   Yes - demil/mli   Fig:	2 amplifier, operational, general purpose
Voltage Rating And Type Per Characteristic:22.0 volts power sourceTest Data Document:96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards)7erminal Type And Quantity:20 leadlessShelf Life:N/aUnit Of Measure:Pemilitarization:Yes - demil/mliFig:	Terminal Surface Treatment:
22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer in Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	Solder
Test Data Document:   96906-mil-std-883 standard (includes industry or association standards, individual manufactureer in the treminal Type And Quantity:   20 leadless   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   Yes - demil/mli   Fig:	Voltage Rating And Type Per Characteristic:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer in the second standards) individual manufactureer in the second standards individual manufactureer is a second standard standard standard standard standard standards individual manufactureer is a second standard standard standard standard standard standard standard standard standards individual manufacture is a second standard standard standard standard standard standard standard standards individual manufacture is a second standard	22.0 volts power source
Terminal Type And Quantity:   20 leadless   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   Yes - demil/mli   Fiig:	Test Data Document:
20 leadless Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	96906-mil-std-883 standard (includes industry or association standards, individual manufactureer
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   Yes - demil/mli   Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	20 leadless
Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
 Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
-	Yes - demil/mli
A458a0	Fiig:
	A458a0