NSN 5962-01-396-6977

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-396-6977

Operating Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
Pacer dawn
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Criticality Code Justification:
Feat
Design Function And Quantity:
1 transceiver
Case Outline Source And Designator:
D-9 mil-m-38510
Product Name:
rioduct Name.
High performance parity bus transceivers, monolithic silicon
High performance parity bus transceivers, monolithic silicon
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic:
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features:
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features: Esd
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features: Esd Terminal Type And Quantity:
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features: Esd Terminal Type And Quantity: 24 printed circuit
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features: Esd Terminal Type And Quantity: 24 printed circuit Shelf Life:
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features: Esd Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features: Esd Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features: Esd Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a Unit Of Measure:
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features: Esd Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:
High performance parity bus transceivers, monolithic silicon Voltage Rating And Type Per Characteristic: 4.5 volts total supply and 5.5 volts total supply Special Features: Esd Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: No