# NSN 5962-01-396-8606

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-396-8606

# Body Length:

0.840 inches

# **Body Width:**

Between 0.220 inches and 0.310 inches

# **Body Height:**

0.185 inches

# **Maximum Power Dissipation Rating:**

500.0 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

High speed

#### **Inclosure Material:**

# Ceramic

Inclosure Configuration:

Dual-in-line

# **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

# **Design Function And Quantity:**

2 shift register

# Case Outline Source And Designator:

D-2 mil-m-38510

# Current Rating Per Characteristic:

25.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

### **Terminal Surface Treatment:**

Solder

# **Product Name:**

Advanced high-speed cmos, dual 4-stage shift register

# Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

### **Special Features:**

4-stage

### Test Data Document:

81349-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

### **Terminal Type And Quantity:**

16 printed circuit

# Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5962-01-396-8606

Digital Microcircuit - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0

