NSN 5962-01-397-0238

Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-397-0238

Body Length:
1.280 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Storage Tempurature Range:
-65.0 to 150.0 degrees celsius
Features Provided:
W/clock and electrostatic sensitive and burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
5 input
5 input Design Function And Quantity:
Design Function And Quantity:
Design Function And Quantity: 1 converter, analog to digital
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment:
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source Test Data Document:
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity:
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 24 printed circuit
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 24 printed circuit Shelf Life:
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a Unit Of Measure:
Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: