# NSN 5962-01-398-3266

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-398-3266

## **Body Length:**

Between 0.554 inches and 0.572 inches

## Body Width:

Between 0.554 inches and 0.572 inches

## **Body Height:**

Between 0.055 inches and 0.125 inches

# Maximum Power Dissipation Rating:

1.0 watts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Static operation and electrostatic sensitive and w/disable and w/enable and high impedance

### Inclosure Material:

Ceramic

## Inclosure Configuration:

Leadless flat pack

## **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

## Input Circuit Pattern:

24 input

# Current Rating Per Characteristic:

185.00 milliamperes reverse current, dc absolute

## **Terminal Surface Treatment:**

Solder

## **Product Name:**

Dual port static ram, master

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

## **Capitance Rating Per Characteristic:**

11.00 input picofarads and 11.00 output picofarads

## **Time Rating Per Chacteristic:**

45.00 nanoseconds access

### Memory Device Type:

Ram

## Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## Terminal Type And Quantity:

48 leadless

#### Shelf Life:

N/a

# NSN 5962-01-398-3266

Memory Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

