NSN 5962-01-398-9060

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-398-9060

Body Length: 1.280 inches Body Width: Between 0.220 inches and 0.310 inches Body Height: 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Between 0.220 inches and 0.310 inches Body Height: 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic:
Between 0.220 inches and 0.310 inches Body Height: 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Body Height: 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
500.0 milliwatts Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
-55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Storage Tempurature Range: -65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
-65.0 to 150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Features Provided: Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Monolithic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Inclosure Configuration: Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Dual-in-line Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Input Circuit Pattern: 15 input Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Design Function And Quantity: 2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
2 converter, digital to analog Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Case Outline Source And Designator: D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
D-9 mil-m-38510 Current Rating Per Characteristic: 2.00 milliamperes supply
Current Rating Per Characteristic: 2.00 milliamperes supply
2.00 milliamperes supply
Terminal Surface Treatment:
Solder
Product Name:
Buffered multiplying d/a converter
Voltage Rating And Type Per Characteristic:
-17.0 volts power source and 17.0 volts power source
Capitance Rating Per Characteristic:
15.00 input picofarads
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 printed circuit
Shelf Life:

N/a

NSN 5962-01-398-9060

Digital-linear Microcircuit - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A458a0