NSN 5962-01-399-4513

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-399-4513

В					

Between 0.397 inches and 0.414 inches

Body Width:

Between 0.291 inches and 0.300 inches

Body Height:

0.101 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Tempurature Range:

-25.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Seawolf class ssn; los angeles class ssn (688); spruance class dd (963); arleigh burke class ddg; landing craft air cushion (lcac); oliver perry class ffg; nimitz class cvn; ticonderoga class cg (47); forrestal class cv

Features Provided:

Electrostatic sensitive and w/enable and 3-state output and high speed and high performance

Inclosure Material:

Plastic

Inclosure Configuration:

Flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Quad 2 input

Criticality Code Justification:

Feat

Design Function And Quantity:

1 selector, data, multiplexer

Current Rating Per Characteristic:

75.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

10.00 input picofarads and 15.00 output picofarads

Special Features:

Weapon system essential

Terminal Type And Quantity:

16 gullwing

Shelf Life:

N/a

NSN 5962-01-399-4513

Digital Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0