NSN 5962-01-406-2428

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-406-2428 **Body Length:** 0.540 inches **Body Width:** 0.300 inches **Body Height:** 0.100 inches **Maximum Power Dissipation Rating:** 706.00 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and bipolar and 3-state output **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Design Function And Quantity:** 1 transceiver **Current Rating Per Characteristic:** 96.00 milliamperes peak forward surge current horsepower metric **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, digital, bipolar cmos, octal bus transceiver, ttl compatible, monolithic silicon Voltage Rating And Type Per Characteristic: 0.5 volts power source and 7.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 flat leads Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig:

A458a0