NSN 5962-01-406-6269

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-406-6269

Body Length:

Between 1.600 inches and 1.630 inches

Body Width:

Between 0.660 inches and 0.680 inches

Body Height:

0.150 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Nha circuit card p/n 680-1035-021 cage 78711, e/i ow-110/a intercommunication group; joint stars

Features Provided:

Electrostatic sensitive and radiation sensitive and burn in

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

28 input

Current Rating Per Characteristic:

20.00 microamperes reverse current, dc microamperes

Product Name:

Microcircuit, custom design, cmos, memor (Isi)

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

10.00 input picofarads and 90.00 output picofarads

Memory Device Type:

First-in first-out

Memory Capacity:

16 bits wide by 32 bits deep

Test Data Document:

78711--235a816 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

64 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5962-01-406-6269

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0