## NSN 5962-01-407-1027

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-407-1027

view Offilite at https://defobasegroup.com/nsi//0302-01-407-1027
Body Length:
Between 0.920 inches and 1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.070 inches and 0.185 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Static operation and electrostatic sensitive and w/enable and high speed
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
18 input
Current Rating Per Characteristic:
120.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
5.00 input picofarads and 7.00 output picofarads
Time Rating Per Chacteristic:
20.00 nanoseconds access
Memory Device Type:
Ram
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5962-01-407-1027

Memory Microcircuit - Page 2 of 2



Demilitarization:

No

Fiig:

A458a0