## NSN 5962-01-407-1034

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-407-1034

View Online at https://aerobasegroup.com/nsn/5962-01-407-1034
Body Length:
Between 0.235 inches and 0.260 inches
Body Width:
Between 0.235 inches and 0.260 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
350.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
2 channel
Design Function And Quantity:
2 switch, double pole single throw normally closed
Case Outline Source And Designator:
F-2a mil-m-38510
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
36.0 volts input/output differential
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 flat leads
Specification Data:

Unit Of Measure:

N/a

Shelf Life:

81349-mil-m-38510/111 government specification

## NSN 5962-01-407-1034

Linear Microcircuit - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A458a0