## NSN 5962-01-407-3742

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-407-3742 **Body Length:** 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and static operation and low power and high speed and high impedance and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 17 input **Current Rating Per Characteristic:** 20.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Capitance Rating Per Characteristic:** 5.00 input picofarads and 6.00 output picofarads **Time Rating Per Chacteristic:** 85.00 nanoseconds access **Memory Device Type:** Ram **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5962-01-407-3742

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0