NSN 5962-01-408-3555

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-408-3555
Body Length:
0.390 inches
Body Width:
Between 0.235 inches and 0.260 inches
Body Height:
Between 0.045 inches and 0.115 inches
Maximum Power Dissipation Rating:
200.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, nand
Case Outline Source And Designator:
F-2a mil-m-38510
Current Rating Per Characteristic:
10.00 milliamperes forward current, nonrepetitive, peak total value absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 15.5 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 pin
Specification Data:
81349-mil-m-38510/50 government specification
Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-408-3555

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0