## NSN 5962-01-408-5198

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-408-5198

Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Design Function And Quantity:
1 multiplexer
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
Voltage Rating And Type Per Characteristic: 7.0 volts power source
7.0 volts power source
7.0 volts power source  Special Features:
7.0 volts power source  Special Features:  16 x 16
7.0 volts power source  Special Features:  16 x 16  Terminal Type And Quantity:
7.0 volts power source  Special Features:  16 x 16  Terminal Type And Quantity:  64 printed circuit
7.0 volts power source  Special Features:  16 x 16  Terminal Type And Quantity:  64 printed circuit  Shelf Life:
7.0 volts power source  Special Features:  16 x 16  Terminal Type And Quantity:  64 printed circuit  Shelf Life:  N/a
7.0 volts power source  Special Features:  16 x 16  Terminal Type And Quantity:  64 printed circuit  Shelf Life:  N/a  Unit Of Measure:
7.0 volts power source  Special Features:  16 x 16  Terminal Type And Quantity:  64 printed circuit  Shelf Life:  N/a  Unit Of Measure:
7.0 volts power source  Special Features:  16 x 16  Terminal Type And Quantity:  64 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
7.0 volts power source  Special Features:  16 x 16  Terminal Type And Quantity:  64 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli
7.0 volts power source  Special Features:  16 x 16  Terminal Type And Quantity:  64 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig: