NSN 5962-01-412-4797

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-412-4797

Body Length: 0.101 millimeters Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius End Application: Apn232, rf assembly Features Provided:	
Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius End Application: Apn232, rf assembly	
500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius End Application: Apn232, rf assembly	
Operating Tempurature Range: -55.0/+125.0 degrees celsius End Application: Apn232, rf assembly	
-55.0/+125.0 degrees celsius End Application: Apn232, rf assembly	
End Application: Apn232, rf assembly	
Apn232, rf assembly	
Features Provided:	
i catalog i loviaca.	
Electrostatic sensitive and burn in, mil-std-883, class b	
Criticality Code Justification:	
Cbbl	
Current Rating Per Characteristic:	
2.00 nanoamperes average forward current averaged over a full 60-hz cycle absolute and 2.00 nanoamperes average	verage forward current
averaged over a full 60-hz cycle outside diameter	
Product Name:	
Microcircuit die, op amp, low offset	
Voltage Rating And Type Per Characteristic:	
40.0 volts input offset over operating temp	
Supplementary Features:	
Die size 65 x 101 mils; power consumption 120 mw; differential input voltage 30v	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A458a0	