## NSN 5962-01-414-6442

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-414-6442 **Body Length:** 1.490 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** 0.217 inches **Maximum Power Dissipation Rating:** 470.0 milliwatts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **End Application:** C10661b/aas38 **Features Provided:** Electrostatic sensitive and bipolar and unipolar and w/resistor **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Design Function And Quantity:** 1 converter, analog to digital and 1 control, interface **Case Outline Source And Designator:** D-10 mil-m-38510 **Terminal Surface Treatment:** Solder **Product Name:** A/d converter with microprocessor interface **Voltage Rating And Type Per Characteristic:** -24.0 volts input and 24.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5962-01-414-6442 Digital-linear Microcircuit - Page 2 of 2



Fiig:

A458a0