NSN 5962-01-414-8326

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-414-8326

Body Length:	
Between 0 640 inches and 0 662 inches	

Body Width:

Between 0.640 inches and 0.662 inches

Body Height:

Between 0.064 inches and 0.120 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Pacer dawn

Features Provided:

Monolithic and burn in

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

24 input

Criticality Code Justification:

Feat

Design Function And Quantity:

1 microprocessor

Case Outline Source And Designator:

C-5 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuits, digital, cmos, 4-bit slice microprocessor, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Chacteristic:

27.00 nanoseconds propagation delay

Special Features:

Esd

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-414-8326

Digital Microcircuit - Page 2 of 2



Terminal Type And Quantity:
44 leadless
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A458a0