## NSN 5962-01-414-9720

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-414-9720 **Body Length:** 2.530 inches **Body Width:** 2.530 inches **Body Height:** Between 0.110 inches and 2.790 inches **Maximum Power Dissipation Rating:** 5.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** F-16 acft **Features Provided:** Electrostatic sensitive and w/clock **Inclosure Configuration:** Leaded chip carrier **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Criticality Code Justification:** Cbbl **Design Function And Quantity:** 3 microprocessor **Terminal Surface Treatment:** Solder **Product Name:** 

Microcircuit, digital, microprocessor, risc, 32-bit

**Voltage Rating And Type Per Characteristic:** 

-0.5 volts total supply and 7.0 volts total supply

**Special Features:** 

Consists of 3 tightly-coupled processors, 32-bit cpu, sys ctl coprocessor, & a floating point accelerator; nha p/n 3129303, 3129304,

3129305; used on p/ns 3405 & 0500

**Test Data Document:** 

96906-mil-std883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

172 gullwing

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

## NSN 5962-01-414-9720

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0