## NSN 5962-01-415-6263

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-415-6263 **Body Length:** Between 0.250 inches and 0.260 inches **Body Width:** Between 0.250 inches and 0.260 inches **Body Height:** 0.083 inches **Maximum Power Dissipation Rating:** 600.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 comparator **Current Rating Per Characteristic:** 20.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable **Terminal Surface Treatment:** Solder **Product Name:** Ultrafast comparator **Voltage Rating And Type Per Characteristic:** -7.0 volts power source and 7.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 gullwing Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5962-01-415-6263

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0