## NSN 5962-01-415-9701

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-415-9701 **Body Length:** Between 0.990 inches and 1.030 inches **Body Width:** Between 0.990 inches and 1.030 inches **Body Height:** 0.015 inches **Maximum Power Dissipation Rating:** 1.5 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** B-2 bomber, instrument support equipment **Features Provided:** Electrostatic sensitive and 3-state output and w/clock and bidirectional **Inclosure Material:** Ceramic **Inclosure Configuration:** Leaded chip carrier **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Criticality Code Justification:** Feat **Design Function And Quantity:** 1 microprocessor **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Special Features:** Nuclear hardness critical process **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 68 gullwing Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 5962-01-415-9701

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0