

View Online at <https://aerobasegroup.com/nsn/5962-01-417-6397>

**Body Length:**

0.785 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

0.200 inches

**Maximum Power Dissipation Rating:**

1375.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

F-16

**Features Provided:**

Burn in, mil-std-883, class b and electrostatic sensitive and hermetically sealed and monolithic and tested to mil-std-883

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

8 input

**Criticality Code Justification:**

Cbbl

**Design Function And Quantity:**

4 comparator, differential

**Case Outline Source And Designator:**

D-1 mil-m-38510

**Current Rating Per Characteristic:**

20.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, linear, quad differential comparator, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

18.0 volts power source

**Time Rating Per Characteristic:**

1300.00 nanoseconds response

**Special Features:**

Case outline source and designator is mil-std-883

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0