

View Online at <https://aerobasegroup.com/nsn/5962-01-417-6397>

Body Length:

0.785 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.200 inches

Maximum Power Dissipation Rating:

1375.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

F-16

Features Provided:

Burn in, mil-std-883, class b and electrostatic sensitive and hermetically sealed and monolithic and tested to mil-std-883

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

8 input

Criticality Code Justification:

Cbbl

Design Function And Quantity:

4 comparator, differential

Case Outline Source And Designator:

D-1 mil-m-38510

Current Rating Per Characteristic:

20.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, linear, quad differential comparator, monolithic silicon

Voltage Rating And Type Per Characteristic:

18.0 volts power source

Time Rating Per Characteristic:

1300.00 nanoseconds response

Special Features:

Case outline source and designator is mil-std-883

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0