

View Online at <https://aerobasegroup.com/nsn/5962-01-420-6395>

Body Length:

Between 0.442 inches and 0.460 inches

Body Width:

Between 0.442 inches and 0.460 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Pacer dawn

Features Provided:

Burn in, mil-std-883, class b and electrostatic sensitive and monolithic and programmed and tested to mil-std-883

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

12 input

Criticality Code Justification:

Cbbl

Case Outline Source And Designator:

C-4 mil-m-38510

Current Rating Per Characteristic:

120.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, programmed (cy7c245-35)

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source and -3.0 volts input and 7.0 volts input

Capitance Rating Per Characteristic:

6.00 input picofarads and 8.00 output picofarads

Time Rating Per Characteristic:

35.00 nanoseconds af output megawatts

Memory Device Type:

Prom

Special Features:

Altered item programmed using 67268 5962-88735033a

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0