NSN 5962-01-420-9506

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-420-9506

Operating Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
Pacer dawn
Features Provided:
Electrostatic sensitive
Inclosure Configuration:
Leadless flat pack
Criticality Code Justification:
Cbbl
Product Name:
Programmed pal
Voltage Rating And Type Per Characteristic:
5.0 volts power source
Memory Device Type:
Pal
Special Features:
Special Features: Altered item made from 5962-87682012a, cage 67268
Altered item made from 5962-87682012a, cage 67268
Altered item made from 5962-87682012a, cage 67268 Terminal Type And Quantity:
Altered item made from 5962-87682012a, cage 67268 Terminal Type And Quantity: 20 leadless
Altered item made from 5962-87682012a, cage 67268 Terminal Type And Quantity: 20 leadless Shelf Life:
Altered item made from 5962-87682012a, cage 67268 Terminal Type And Quantity: 20 leadless Shelf Life: N/a
Altered item made from 5962-87682012a, cage 67268 Terminal Type And Quantity: 20 leadless Shelf Life: N/a
Altered item made from 5962-87682012a, cage 67268 Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure:
Altered item made from 5962-87682012a, cage 67268 Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization:
Altered item made from 5962-87682012a, cage 67268 Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: No