## NSN 5962-01-420-9628

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-420-9628

| Вс  | ody Length:   |
|-----|---|
| 0.3 | 358 inches  |
| Вс  | ody Width:  |
| 0.3 | 358 inches  |
| Вс  | ody Height:   |
| 0.1 | 100 inches  |
| Ма  | aximum Power Dissipation Rating:  |
| 1.0 | 04 watts  |
| Op  | perating Tempurature Range:   |
| -5  | 5.0/+125.0 degrees celsius  |
| St  | orage Tempurature Range:  |
| -6  | 5.0/+150.0 degrees celsius  |
| En  | nd Application:   |
| Pa  | acer dawn   |
| Fe  | eatures Provided:   |
| He  | ermetically sealed and burn in and programmable and 3-state output and monolithic and electrostatic sensitive |
| Ine | closure Configuration:  |
| Le  | eadless flat pack   |
| Οι  | utput Logic Form:   |
| Tra | ansistor-transistor logic   |
| Inj | put Circuit Pattern:  |
| 14  | l input   |
| Cr  | riticality Code Justification:  |
| Cb  | bl  |
| Те  | erminal Surface Treatment:  |
| Sc  | blder   |
| Vc  | oltage Rating And Type Per Characteristic:  |
| -0. | .3 volts power source and 7.0 volts power source  |
| Me  | emory Device Type:  |
| Pa  | al  |
| Те  | erminal Type And Quantity:  |
| 28  | Bleadless   |
| Sh  | nelf Life:  |
| N/  | /a  |
| Ur  | nit Of Measure:   |
|     |   |
| De  | emilitarization:  |
| No  |   |
| Fii | ig:   |
| A4  | 458a0   |