

View Online at <https://aerobasegroup.com/nsn/5962-01-423-2614>

**Body Length:**

1.485 inches

**Body Width:**

0.225 inches

**Body Height:**

Between 0.240 inches and 0.310 inches

**Maximum Power Dissipation Rating:**

1.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Agm 130

**Features Provided:**

Burn in, mil-std-883, class b and beam lead chip and erasable and monolithic and programmed and tested to mil-std-883 and ultraviolet erasable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

14 input

**Criticality Code Justification:**

Cbbl

**Case Outline Source And Designator:**

D-15 mil-m-38510

**Current Rating Per Characteristic:**

120.00 milliamperes reverse current, dc absolute and 35.00 milliamperes reverse current, dc blank

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit-erasable programmable read only memory

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source and -3.0 volts input and 7.0 volts input

**Capitance Rating Per Characteristic:**

10.00 input picofarads and 10.00 output picofarads

**Time Rating Per Characteristic:**

55.00 nanoseconds access

**Memory Device Type:**

Eprom

**Special Features:**

Altered item made from 67268 5962-8953702yx; case outline source and designator is mil-std-1835 cdip3-t28 or gdip4-t28

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

28 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0