

View Online at <https://aerobasegroup.com/nsn/5962-01-423-2614>

Body Length:

1.485 inches

Body Width:

0.225 inches

Body Height:

Between 0.240 inches and 0.310 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Agm 130

Features Provided:

Burn in, mil-std-883, class b and beam lead chip and erasable and monolithic and programmed and tested to mil-std-883 and ultraviolet erasable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

14 input

Criticality Code Justification:

Cbbl

Case Outline Source And Designator:

D-15 mil-m-38510

Current Rating Per Characteristic:

120.00 milliamperes reverse current, dc absolute and 35.00 milliamperes reverse current, dc blank

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit-erasable programmable read only memory

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source and -3.0 volts input and 7.0 volts input

Capitance Rating Per Characteristic:

10.00 input picofarads and 10.00 output picofarads

Time Rating Per Characteristic:

55.00 nanoseconds access

Memory Device Type:

Eprom

Special Features:

Altered item made from 67268 5962-8953702yx; case outline source and designator is mil-std-1835 cdip3-t28 or gdip4-t28

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0