

View Online at <https://aerobasegroup.com/nsn/5962-01-424-9750>

**Body Length:**

0.358 inches

**Body Width:**

0.100 inches

**Maximum Power Dissipation Rating:**

250.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Pacer dawn

**Features Provided:**

Electrostatic sensitive and low power and schottky and tested to mil-std-883 and w/register output and w/storage and burn in and monolithic and hermetically sealed

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Transistor-transistor logic

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

1 shift register, parallel in, parallel out

**Case Outline Source And Designator:**

C-2 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, low power schottky ttl, 8 bit shift register with parallel inputs and input latches

**Voltage Rating And Type Per Characteristic:**

4.5 volts power source and 5.5 volts power source

**Special Features:**

Esd

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A458a0