

View Online at <https://aerobasegroup.com/nsn/5962-01-425-2796>

Body Length:

0.358 inches

Body Width:

0.358 inches

Body Height:

0.100 inches

Maximum Power Dissipation Rating:

450.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Pacer dawn

Features Provided:

Electrostatic sensitive and tested to mil-std-883 and burn in, mil-std-883, class b and monolithic

Inclosure Material:

Silicon

Inclosure Configuration:

Leadless flat pack

Criticality Code Justification:

Cbbl

Design Function And Quantity:

1 converter, digital to analog

Case Outline Source And Designator:

C-2 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, linear, digital to analog converter, monolithic silicon

Voltage Rating And Type Per Characteristic:

4.5 volts power source and 15.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A458a0