NSN 5962-01-425-4055

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-425-4055

-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Pacer dawn Features Provided: Electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A458a0	Operating Tempurature Range:
End Application: Pacer dawn Features Provided: Electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-55.0/+125.0 degrees celsius
End Application: Pacer dawn Features Provided: Electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Storage Tempurature Range:
Pacer dawn Features Provided: Electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-65.0/+150.0 degrees celsius
Features Provided: Electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	End Application:
Electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Pacer dawn
Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Features Provided:
Ceramic Inclosure Configuration: Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Electrostatic sensitive
Inclosure Configuration: Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Material:
Leadless flat pack Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ceramic
Criticality Code Justification: Cbbl Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Configuration:
Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Leadless flat pack
Design Function And Quantity: 1 microprocessor Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Criticality Code Justification:
Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cbbl
Terminal Surface Treatment: Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Design Function And Quantity:
Solder Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1 microprocessor
Product Name: Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Surface Treatment:
Cascadable signal processor Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Solder
Voltage Rating And Type Per Characteristic: 0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Product Name:
0.0 volts power source and 7.0 volts power source Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cascadable signal processor
Terminal Type And Quantity: 84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Voltage Rating And Type Per Characteristic:
84 wire lead Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.0 volts power source and 7.0 volts power source
Specification Data: 99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
99971-7555164 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	84 wire lead
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	99971-7555164 manufacturers specification control
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A458a0	Fiig:
	A458a0