

View Online at <https://aerobasegroup.com/nsn/5962-01-425-8839>

Body Length:

Between 0.940 inches and 0.960 inches

Body Width:

Between 0.940 inches and 0.960 inches

Body Height:

Between 0.067 inches and 0.083 inches

Maximum Power Dissipation Rating:

750.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Pacer dawn

Features Provided:

Burn in, mil-std-883, class b and compatible dtl and compatible rtl and electrostatic sensitive and monolithic and tested to mil-std-883 and 3-state output and w/clock

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

39 input

Criticality Code Justification:

Cbbl

Design Function And Quantity:

1 multiplier

Case Outline Source And Designator:

C-7 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, radix butterfly cmos, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.3 volts power source and 7.0 volts power source and -0.3 volts input and 3.0 volts input

Time Rating Per Characteristic:

40.00 nanoseconds propagation delay

Special Features:

16-bit arithmetic unit capable of calculating complex multiplications, radix 2 butterflies, radix 4 butterflies and inverse radix 4 butterflies; 10mhz clock frequency

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

68 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0