Hybrid Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-426-7254

| View Online at https://aerobasegroup.com/nsn/5962-01-426-7254 |
|--|
| Body Length: |
| 1.900 inches |
| Body Width: |
| 1.000 inches |
| Body Height: |
| 0.215 inches |
| Maximum Power Dissipation Rating: |
| 2.2 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| NHA5-99-801-4567 |
| Features Provided: |
| Electrostatic sensitive and radiation sensitive |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Design Function And Quantity: |
| 1 transceiver |
| Product Name: |
| Microcircuit hybrid, linear mil-std-1553, bc/rtu/mt multiplexed terminal |
| Voltage Rating And Type Per Characteristic: |
| 4.5 volts applied and 5.5 volts applied |
| Hybrid Technology Type: |
| Monolithic |
| Special Features: |
| Multiple supply voltages |
| Terminal Type And Quantity: |
| 70 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A458a0 |
| |