

View Online at <https://aerobasegroup.com/nsn/5962-01-430-5507>

Body Length:

1.060 inches

Body Width:

0.310 inches

Body Height:

0.200 inches

Maximum Power Dissipation Rating:

303.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Pacer dawn

Features Provided:

Electrostatic sensitive and tested to mil-std-883 and programmed and burn in, mil-std-883, class b and erasable

Inclosure Material:

Silicon

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Bipolar metal-oxide semiconductor

Criticality Code Justification:

Cbbl

Case Outline Source And Designator:

D-8 mil-m-38510

Product Name:

Mckt, digital bipolar, programmablearray logic

Voltage Rating And Type Per Characteristic:

4.5 volts power source and 5.5 volts power source

Memory Device Type:

Pal

Special Features:

Altered item programmed using 67268/5962-8851501rx using version or firmware description document vdd0236.02..01

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A458a0