NSN 5962-01-431-9181

Memory Microcircuit - Page 1 of 1

No Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-431-9181 **Maximum Power Dissipation Rating:** 2.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **End Application:** Pacer dawn **Features Provided:** Electrostatic sensitive and tested to mil-std-883 and programmed and burn in, mil-std-883, class b and erasable **Inclosure Material:** Silicon **Inclosure Configuration:** Pin grid array **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Criticality Code Justification:** Cbbl **Product Name:** Mckt, digital, uv erasable; cmos; programmed logic device Voltage Rating And Type Per Characteristic: 4.5 volts power source and 5.5 volts power source **Memory Device Type:** Pal **Special Features:** Altered item programmed using 67268/5962-8946901yx using firmware version/description document fdd/vdd 0249-01.02 **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 68 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**