

View Online at <https://aerobasegroup.com/nsn/5962-01-440-1051>

**Body Length:**

1.700 inches

**Body Width:**

Between 0.350 inches and 0.405 inches

**Body Height:**

0.232 inches

**Maximum Power Dissipation Rating:**

1.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

105503296826 e/i fscm 18876

**Features Provided:**

Monolithic and electrostatic sensitive and low power and burn in, mil-std-883, class b

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, memory, digital, cmos, 128k x 8 static random access memory (sram) low power, dual ce

**Voltage Rating And Type Per Characteristic:**

-0.5 volts input and 7.0 volts input

**Time Rating Per Characteristic:**

45.00 nanoseconds access

**Memory Device Type:**

Ram

**Special Features:**

For static ram (sram) 128k x 8 ; monolithic silicon

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

32 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A458a0