NSN 5962-01-444-9547

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-444-9547

| Body Length: |
|--|
| 0.458 inches |
| Body Width: |
| 0.458 inches |
| Body Height: |
| 0.180 inches |
| Maximum Power Dissipation Rating: |
| 1.5 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| F-15i |
| Features Provided: |
| Electrostatic sensitive and ultraviolet erasable and programmable and monolithic |
| Inclosure Material: |
| Silicon |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 24 input |
| Criticality Code Justification: |
| Cbbl |
| Case Outline Source And Designator: |
| D-15 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Firmware, microcircuit, digital-programmable logic |
| Voltage Rating And Type Per Characteristic: |
| -2.0 volts total supply and 7.0 volts total supply |
| Memory Device Type: |
| Pal |
| Special Features: |
| Altered item, make from 5962-9061102yx, fielded software (pof file) version identification 8521165.101 |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 00 artists districtly |

28 printed circuit

NSN 5962-01-444-9547

Memory Microcircuit - Page 2 of 2



| | | | | - |
|-----|----|-----|-----|-----|
| C I | 20 | lŧ. | l i | fe: |
| J. | 16 | | _, | ıc. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0