

View Online at <https://aerobasegroup.com/nsn/5962-01-445-6152>

Body Length:

Between 0.442 inches and 0.460 inches

Body Width:

Between 0.442 inches and 0.460 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

F-15i

Features Provided:

Burn in, mil-std-883, class b and electrostatic sensitive and hermetically sealed and monolithic and tested to mil-std-883 and fast carry and 3-state output

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

16 input

Criticality Code Justification:

Cbbl

Design Function And Quantity:

8 transceiver and 8 register

Case Outline Source And Designator:

C-4 mil-m-38510

Current Rating Per Characteristic:

260.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, fast cmos octal transceiver/register, three-state outputs, ttl compatible inputs and limited output voltage swing, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts input and 0.5 volts input and -0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

10.00 input picofarads and 12.00 output picofarads

Time Rating Per Characteristic:

1.50 nanoseconds propagation delay and 6.00 nanoseconds propagation delay

Special Features:

Case outline source and designator is mil-std-1835, cccc1-n28

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 leadless

Specification Data:

67268-5962-92246 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0