## NSN 5962-01-445-9587

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-445-9587

**Body Length:** 

Between 1.040 inches and 1.080 inches

**Body Width:** 

Between 1.040 inches and 1.080 inches

**Body Height:** 

Between 0.215 inches and 0.345 inches

**Maximum Power Dissipation Rating:** 

760.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**End Application:** 

F-15i

**Features Provided:** 

Burn in, mil-std-883, class b and electrostatic sensitive and hermetically sealed and monolithic and tested to mil-std-883 and bipolar and 3-state output

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Pin grid array

**Output Logic Form:** 

Bipolar metal-oxide semiconductor

**Criticality Code Justification:** 

Cbbl

**Case Outline Source And Designator:** 

P-pb mil-m-38510

**Current Rating Per Characteristic:** 

-40.00 milliamperes collector cutoff current, dc, base open not applicable and -180.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable and -1.00 microamperes collector cutoff current, dc, with specified resistance between base and emitter microamperes and 1.00 microamperes reverse current, dc microamperes

**Terminal Surface Treatment:** 

Solder

**Product Name:** 

Microcircuit, memory, digital, bicmos, 512 x 18 x 2 clocked fifo, monolithic silicon

**Voltage Rating And Type Per Characteristic:** 

-0.5 volts input and 5.5 volts input and -0.5 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:** 

10.50 input picofarads

Time Rating Per Chacteristic:

1.50 nanoseconds input to output access and 18.00 nanoseconds input to output access

**Memory Device Type:** 

First-in first-out

**Special Features:** 

Case outline source and designator is miletd-1835, cmga15-np; clock speed of 50 mbz; this item has a nin-85 (c3) as an index alignment

## NSN 5962-01-445-9587

Memory Microcircuit - Page 2 of 2



Test	Data	Docum	ent
------	------	-------	-----

96906-mil-i-38535 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

84 pin

**Specification Data:** 

67268-5962-94704 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A458a0