NSN 5962-01-446-7757

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-446-7757 **Body Length:** Between 0.800 inches and 0.840 inches **Body Width:** Between 0.392 inches and 0.408 inches **Body Height:** Between 0.080 inches and 0.100 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Radar warning system, an/anl-68 (v) -3, litton systems inc **Features Provided:** Monolithic and electrostatic sensitive and low power and burn in, mil-std-883, class b **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, memory, digital, cmos, 128k x 8 static random access memory (sram) low power **Voltage Rating And Type Per Characteristic:** 5.0 volts power source **Time Rating Per Chacteristic:** 45.00 nanoseconds access **Memory Device Type:** Ram **Special Features:** Circuit function-dual ce **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 32 pin

N/a **Unit Of Measure:**

Shelf Life:

NSN 5962-01-446-7757

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0