NSN 5962-01-446-7757

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-446-7757

Body Length:

Between 0.800 inches and 0.840 inches

Body Width:

Between 0.392 inches and 0.408 inches

Body Height:

Between 0.080 inches and 0.100 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Radar warning system, an/anl-68 (v) -3, litton systems inc

Features Provided:

Monolithic and electrostatic sensitive and low power and burn in, mil-std-883, class b

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, memory, digital, cmos, 128k x 8 static random access memory (sram) low power

Voltage Rating And Type Per Characteristic:

5.0 volts power source

Time Rating Per Chacteristic:

45.00 nanoseconds access

Memory Device Type:

Ram

Special Features:

Circuit function-dual ce

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

32 pin

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5962-01-446-7757

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

