NSN 5962-01-447-5768

Memory Microcircuit - Page 1 of 2

Demilitarization: Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-01-447-5768 **Body Length:** 1.060 inches **Body Width:** 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Burn in and electrostatic sensitive and monolithic and programmed **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Current Rating Per Characteristic:** 70.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Overspeed test/relay **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 10.00 nanoseconds acc/pac detector tint control **Memory Device Type:** Pal **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a **Unit Of Measure:**

NSN 5962-01-447-5768

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0