

View Online at <https://aerobasegroup.com/nsn/5962-01-449-1568>

Body Length:

1.485 inches

Body Width:

Between 0.240 inches and 0.310 inches

Body Height:

Between 0.030 inches and 0.215 inches

Maximum Power Dissipation Rating:

1.5 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

F-15i

Features Provided:

Electrostatic sensitive and ultraviolet erasable and low bias and 3-state output and programmed and w/clock

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

24 input

Criticality Code Justification:

Cbbl

Case Outline Source And Designator:

D-15 mil-m-38510

Current Rating Per Characteristic:

225.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, cmos, uv erasable, programmable logic device, programmed

Voltage Rating And Type Per Characteristic:

-2.0 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

10.00 input picofarads and 12.00 output picofarads

Memory Device Type:

Pal

Special Features:

Altered item make from 5962-901102xa, firmware/ version discription document vdd0355-01.00

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0