# NSN 5962-01-450-6525

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-450-6525

# Maximum Power Dissipation Rating:

1.0 milliwatts

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

# End Application:

F-15s

## **Features Provided:**

Electrostatic sensitive and programmed and ultraviolet erasable and burn in

## Inclosure Material:

Ceramic

## Inclosure Configuration:

Dual-in-line

# Input Circuit Pattern:

15 input

### Criticality Code Justification:

Cbbl

### **Terminal Surface Treatment:**

Solder

### Product Name:

Microcircuit, digital-programmable read only memory, uv erasable

### Voltage Rating And Type Per Characteristic:

-0.3 volts power source and 7.0 volts power source

### Time Rating Per Chacteristic:

250.00 nanoseconds access

### Memory Device Type:

Pal

### Special Features:

Altered item make from smd 8202505ya; generic pn 27128 and 27128a and 27c128

### Terminal Type And Quantity:

28 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A458a0