NSN 5962-01-453-5742

Hybrid Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-453-5742

Maximum Dawar Discination Datings
Maximum Power Dissipation Rating:
0.75 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
Usaf f-16 mlu e/i fscm 0fss1
Inclosure Configuration:
Dual-in-line
Design Function And Quantity:
1 driver
Terminal Surface Treatment:
Solder
Product Name:
Pin diode driver
Voltage Rating And Type Per Characteristic:
5.0 volts power source
Hybrid Technology Type:
Trybrid recimology Type.
Monolithic
Monolithic
Monolithic Precious Material And Location:
Monolithic Precious Material And Location: Internal surfaces gold
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity:
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity: 22 gullwing
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity: 22 gullwing Shelf Life:
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity: 22 gullwing Shelf Life: N/a
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity: 22 gullwing Shelf Life: N/a
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity: 22 gullwing Shelf Life: N/a Unit Of Measure:
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity: 22 gullwing Shelf Life: N/a Unit Of Measure: Demilitarization:
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity: 22 gullwing Shelf Life: N/a Unit Of Measure: Demilitarization: No
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity: 22 gullwing Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Monolithic Precious Material And Location: Internal surfaces gold Terminal Type And Quantity: 22 gullwing Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: