Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-453-6192

Maximum Power Dissipation Rating:

1.9 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

P/n 4007234-1 e/i fscm 67268

Features Provided:

Monolithic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Design Function And Quantity:

1 memory, electrically erasable programmable rom

Terminal Surface Treatment:

Gold

Product Name:

Microcircuit, memory, digital, cmos, electrically erasable programmable, logic device, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts input and 7.0 volts input

Precious Material And Location:

Terminals gold

Supplementary Features:

Eecmos 2, 000 gate in-system programmable logic device with clock frequency of 60mhz

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

44 j-hook

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A458a0