NSN 5962-01-453-9546

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-453-9546

1.0 watts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: 1055-01-256-9756 Inclosure Configuration: Dual-in-line
-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: 1055-01-256-9756 Inclosure Configuration:
Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: 1055-01-256-9756 Inclosure Configuration:
-65.0/+150.0 degrees celsius End Application: 1055-01-256-9756 Inclosure Configuration:
End Application: 1055-01-256-9756 Inclosure Configuration:
1055-01-256-9756 Inclosure Configuration:
Inclosure Configuration:
Dual-in-line
Dual III III C
Design Function And Quantity:
1 control
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, linear, high speed pulse width modulator controller, monolithic silicon
Voltage Rating And Type Per Characteristic:
12.0 volts input and 22.0 volts input
Test Data Document:
$96906 \hbox{-mil-std-}883 \ standard \ (includes \ industry \ or \ association \ standards, \ individual \ manufactureer \ standards, \ etc.).$
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0