

View Online at <https://aerobasegroup.com/nsn/5962-01-454-2089>

**Maximum Power Dissipation Rating:**

2.2 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Electrical e/i fscm 67268

**Features Provided:**

Hybrid

**Inclosure Configuration:**

Single-in-line

**Design Function And Quantity:**

1 memory, first in-first out

**Terminal Surface Treatment:**

Gold

**Product Name:**

Microcircuit, hybrid, digital, static radom access memory, cmos 128k x 32-bit

**Voltage Rating And Type Per Characteristic:**

-0.5 volts input and 7.0 volts input

**Hybrid Technology Type:**

Monolithic

**Special Features:**

Sram, 128k x 32-bit, access time 25 ns, package style hex-in-line, single cavity, with standoff

**Precious Material And Location:**

Terminal gold

**Test Data Document:**

96906-mil-std-88 3 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

66 case

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A458a0