NSN 5962-01-454-3947

Microcircuit Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-454-3947

| Body Length: | |
|--|---|
| .950 inches | |
| Body Width: | |
| .950 inches | |
| Body Height: | |
| .115 inches | |
| Operating Tempurature Range: | |
| 55.0/+125.0 degrees celsius | |
| storage Tempurature Range: | |
| 65.0/+150.0 degrees celsius | |
| nd Application: | |
| /F1-8D-CN,-5998 | |
| eatures Provided: | |
| lectrostatic sensitive and w/clock and w/register output | |
| nclosure Material: | |
| Ceramic and metal | |
| nclosure Configuration: | |
| eadless flat pack | |
| Dutput Logic Form: | |
| ransistor-transistor logic | |
| nput Circuit Pattern: | |
| input | |
| Design Function And Quantity: | |
| gate, array | |
| erminal Surface Treatment: | |
| Solder | |
| licrocircuit Device Type And Quantity: | |
| digital | |
| oltage Rating And Type Per Characteristic: | |
| .0 volts power source and 7.0 volts power source | |
| est Data Document: | |
| 6906-mil-std-883 standard (includes industry or association standard | s, individual manufactureer standards, etc.). |
| erminal Type And Quantity: | |
| 8 leadless | |
| Shelf Life: | |
| I/a | |
| Init Of Measure: | |
| | |
| Demilitarization: | |
| lo | |
| iig: | |
| 458a0 | |