

View Online at <https://aerobasegroup.com/nsn/5962-01-459-3192>

**Maximum Power Dissipation Rating:**

22.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

1430-01-378-6963 e/i fscm 18876

**Features Provided:**

Dual positive edge triggered and low power and schottky and monolithic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Design Function And Quantity:**

1 flip-flop, edge triggered, d-type

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuits, digital advanced low power schottky ttl, dual d type positive-edge triggered flip-flops with clean andreset monolithic silicon

**Voltage Rating And Type Per Characteristic:**

-0.5 volts input and 7.0 volts input

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0